SUBPART C - DAMS

MO 520.21 Definitions and Classes

NRCS is required by policy and federal law to maintain the National Inventory of Dams. Timely reporting of dam construction is important in developing and managing the engineering workload and workforce in the state. NRCS is currently participating as an advisor to the State Dam Safety Council as they look at revising registration criteria. Accurate and complete data on which to base decisions is needed.

- (f) For the purpose of the National Inventory of Dams (NID) criteria contained in NEM 520.21(f)(2) and (f)(3) the definition of storage is the total volume capacity, in acrefeet, in a reservoir below the lowest planned settled crest elevation of the top of dam. This is the definition used by the U.S. Army Corps of Engineers for the NID.
- (f)(4) Inventory dams will be included in the NRCS inventory if they meet all of the following:
 - (i) Dam was built with NRCS technical and/or financial assistance.
 - (ii) The dam was built according to NRCS standards and specifications in effect at the time of construction.
 - (iii) Alterations to the dam since the time of construction have been made in accordance with NRCS standards and specifications.
- (f)(5) Inventory for new dams.

As new dams are constructed, the required data is to be added to the NRCS inventory on the basis of design and construction records. The individual approving the design shall, to the extent possible, complete Form MO-ENG-C94. The individual making the final construction check will check Form MO-ENG-C94, make any needed as-built corrections, and verify that all items are complete. One copy of Form MO-ENG-C94 is to be forwarded through the area office to the State Conservation Engineer and one copy retained in the case file.

State inventory information will be sent to the Missouri Department of Natural Resources at least annually, by the State Office.

Inventory data will be retrieved as needed by the State Office and copies of the inventory furnished to respective area and field offices.

Data on new dams and updated or corrected data on previously submitted dams can be submitted at any time. Data on all dams completed the past year from September 1 through August 31 must be forwarded through the area office to the State Conservation Engineer by September 30. This data will then be entered into the dam inventory database.

(f)(6) Responsibility.

- (i) The State Conservation Engineer provides overall coordination for the inventory of dams.
- (ii) Each Area Conservationist (AC) insures the inventory policy is carried out by the field offices.
- (iii) Each area office will review the data for each dam received from the field, for completeness and accuracy, before transmitting to the state office.

Instructions for completing Form NRCS-ENGC-94:

All instructions are on form or self explanatory except the Federal Agency I.D. (NRCS I.D.). Additional instructions are contained in Missouri Engineering Forms Handbook. The NRCS I.D. is a 10-character Missouri NRCS identification in accordance with the following:

(i) <u>Watershed Dam</u> - This identification begins with the 2-letter (MO) state abbreviation, followed by a **4-digit project number for the watershed**, followed by 4-digit site number.

Example: Troublesome Creek, Site A5 MO2025A005

(ii) <u>CO-01 Dam</u> - This identification begins with a 2-letter (MO) state abbreviation, followed by a **2-digit program code (01)**, followed by a *3-digit county* number, followed by a 3-digit site number.

Example: Joe Doe in Atchison county and 14th site in county MO01005014

(iii) <u>RC&D Dams</u> - This identification begins with the 2-letter (MO) state abbreviation, followed by a **4-digit project number**, followed by a **4-digit** site number. The site number will be consecutive starting with 0001.

Example: Dam in Green Hills RC&D Project, 3rd dam in project MO60030003

NRCS NATIONAL INVENTORY OF DAMS (for Missouri use)

1) DAM NAME:
2) Other Dam Names: 3) Dam Former Names:
4) Federal Agency ID (NRCS ID): 5) National ID: (Provided by MO Dam Safety)
6) Longitude: (Decimal Degrees) 7) Latitude: (Decimal Degrees)
8) Location: S T 9) County: 10) River/Stream:
11) Nearest City/Town: Miles
13) Owner Name: 14) Owner Type: 15) Dam Designer:
16) Non-Fed Dam on Fed Prop:□Yes □No 17) Dam Type: ^{1/}
18) Dam Core: Position: Type: Certainty: 19) Foundation: Material: Certainty:
20) Purpose: 1/
23) Dam Length, Ft.: 24) Dam Ht., Ft.: ^{_1/} 25) Structural Ht., Ft.: ^{_1/} 26) Hydraulic Ht., Ft.: ^{_1/}
27) Maximum Discharge, cfs: 30) Surface Area, AC:
31) Drainage Area, Sq. Mi.: 32) Down Stream Hazard: \Box L \Box S \Box H
33) Emergency Action Plan (EAP):
34) Last Inspection Date: 35) Inspection Freq.: (Yrs) 36) State Regulated Dam: □Yes □No
37) State Regulatory Agency: 38) Spillway Type: □Uncontrolled □Controlled □None
39) Spillway Width, Ft.: 40) Outlet Gates: ^{_1/} 41) Volume of Dam, CY:
42) Number of Locks: 43) Length of Locks: 44) Lock Width:
Federal Agency (USDA NRCS) Involvement
45) Involvement w/Funding: □Yes □No 46) Involvement w/Design: □Yes □No
47) Involvement w/Construct: □Yes □No 48) Involvement w/Regulatory: □Yes □No
49) Involvement w/Inspection: ☐Yes ☐No 50) Involvement w/Operation: ☐Yes ☐No
51) Involvement as Owner: ☐Yes ☐No 52) Involvement w/Others: ☐Yes ☐No
53) Authorization: □CO-01 □PL-566 □RC&D □WP-03 □PILOT □OTHER
54) PL566 Watershed #: 55) PL566 Watershed Name:
56) Planned Service Life (Yrs): 57) O&M Inspection Responsibility ^{1/} : 58) O&M Current □Yes □No
59) O&M Completed: Omega Yes Omega No 60) Population at Risk 1: 61) Population at Risk Accuracy 1/:
62) Hazard Classification as Designed or Modified: L S H 63) Hazard Classification Year:
65) Sediment Storage, AC.FT.: ^{1/} 66) Flood Storage, AC.FT.: ^{1/}
67) Surcharge Storage, AC.FT.: 68) Other Storage, AC.FT.:
69) Principal Spillway Type: Concrete Pipe (CP) Open Concrete (OC) Corrugated Metal Pipe (CM) None (NO Plastic (PT) Other (OT
70) Auxiliary Spwy #1 Type: Codes: VE - Vegetated RK - Rock ST - Structural
71) Auxiliary Spwy #2 Type: EA - Earth OT - Other NO - None
72) Auxiliary Spwy #3 Type: HR – Hard Rock SR – Soft Rock
73) Conduit Height/Dia:Ft. 74) Conduit Width:Ft. 75) Number of Conduits:
76) Cool Water Release: □Yes □No

 $^{^{1\!/}\!}$ SEE BACK FOR CODE DEFINITIONS

USDA-NRCS

Permit No. To Construct:	Permit No. To C	Permit No. To Operate:			
Remarks:					
	¹ DAM INVENTORY CODE & DEFI	NITIONS			
Owner Type (14) F - Federal S - State L - Local Government (PL-566) U - Public Utility P - Private Owner Foundation (19) Material: R - Rock RS - Rock & Soil S - Soil U - Unlisted/Unknown Certainty: K - Known Z - Estimated	Type of Dam (17) RE – Earth ER – Rockfill PG – Gravity CB – Buttress VA – Arch MV – Multiarch CN – Concrete MS – Masonry RC – Roller Compacted Concrete ST – Stone TC – Timber Crib OT – Other	Core (18) Position: F – Upstream Facing H – Homogenous Dam I – Core X – Unlisted/Unknown Type: A – Bituminous Concrete C – Concrete E – Earth M – Metal P – Plastic X – Unlisted/Unknown Certainty: K – Known Z – Estimated			
Purposes (20) I - Irrigation R - Recreation T - Tailings D - Debris Control C - Flood Control P - Fire Protection S - Water Supply F - Fish & Wildlife O - Other	Year Modified (22) S – Structural F – Foundation E – Seismic H – Hydraulic M – Mechanical O – Other	Outlet Gates (40) X - None L - Vertical Lift S - Slide U - Uncontrolled F - Flap V - Valve O - Other Controlled			

O&M Inspection Respon. (57)

OWNER (if same as field 13)
JOINT (for Owner & NRCS)

G - Grade Control

NRCS OTHER

NONE (No O&M Agreement)

Population At Risk Accuracy (61) Downstream Hazard (32)

E – Estimated

A – Analyzed Breach Map

Hazard Classification (62)

L – Low (NRCS Class a)

S – Significant (NRCS Class b) H – High (NRCS Class c)

- (11) Nearest City or Town Nearest downstream community affected if breach were to occur
- (12) Distance To Nearest City/Town Stream miles to affected town
- (24) Dam Height Top of dam to downstream toe (nearest ft.)
- (25) Structural HT. Top of dam to lowest point of excavated foundation
- (26) Hydraulic HT. Maximum design water level to downstream toe
- (60) Population At Risk All persons exposed to breach flood waters if no evacuation
- (64) EAP Year: Year of most recent review and verification of existing or implementation of new EAP
- (65) Sediment Storage Considered as the volume below the principal spillway elevation
- (66) Flood Storage Volume between principal and auxiliary spillways
- (67) Surcharge Storage Volume between auxiliary spillway and top of dam

\$MO520.23 Classification

- (b)(1) It is important that reasons for assigning a classification be documented. Documentation of the classification is to be one of the following:
 - (i) For non-inventory size Class "a" dams in rural areas with low potential for development, complete Form MO-ENG-46, MO-ENG-C46, or Form MO-ENG-C82.
 - (ii) For non-inventory size Class "a" dams in developing areas use Form MO-ENG-C82. All dams in the following counties with high potential for development shall use Form MO-ENG-C82:

Boone, Buchanan, Camden, Cape Girardeau, Cass, Clay, Cole, Franklin, Greene, Jackson, Jasper, Jefferson, Platte, St. Charles, St. Louis, and Taney.

- (iii) For all job Class IV dams, all Class "a" inventory size dams and all Class "b" and "c" dams, complete Form MO-ENG-C82. A USGS map or equivalent shall be included to show site location and downstream hazards.
- (iv) Written notes addressing all items to be included in the classification documentation may be used for all dams in lieu of the forms.
- (2) Attached is a copy of form MO-ENG-C46 and MO-ENG-C82.

MO-ENG-C82 Rev. 10-03 File Code: 210-13 Page 1 of 2

DOCUMENTATION FOR HAZARD CLASSIFICATION OF DAMS

(PL-566, Job Class IV and Inventory Dams) 114151

Name or Number of Site							
Program (Check One):							
Location: (See attached map or photo)							
County Section NoTR							
Dam in Series: Yes No Explain:							
Preliminary Structure Data							
Assumed Hazard Class ² Drainage Area:	_Acres						
A. Ditch Bottom Elevation at Centerline F. Total Storage to A.S.	CrestAc-Ft.						
B. Ditch Bottom Elevation at Downstream Toe G. Effective Height:	<u>E.</u> – <u>A.</u> =						
C. Floodplain Elevation at Centerline H. Overall Height:	$\underline{\mathbf{D}} \underline{\mathbf{B}}. = \underline{}^{\underline{\mathcal{Y}}}$						
D. Settled Top of Dam Elevation H x S: G. x F.	=						
E. Auxiliary Spillway Crest Elevation Conduit Diameter:	inches						
Job Class(See Form MO-ENG-C12 or C12A)							
Downstream Conditions							
1. Valley Conditions Downstream from Structure: Convergent Diver	gent Parallel						
Floodplain Elevation Valley Slope in Downstream Direction							
2. Stream Channel Size: Depth Width Valley: Width Size	hape						
3. Valley Roughness or Retardance: "n"							
4. First Downstream Hazard (See Page 2 of 2)							
5. Distance Downstream to Junction of Significantly Larger Tributary							
Rationale for Determining Hazard Class							
Actual Hazard Class Analyzed by	Date						
Approved by							
ATTACHED: Breach Routings / Yes / No							
Map(s) Other pertinent supporting documents							

MO-ENG-C82 Rev. 10-03

File Code: 210-13 Page 2 of 2

Describe Type of Utilities, Distance Downstream and Distance Above Floodplain Elevation							mate ce eam eam	Dist Ab Flood	ximate ance ove Iplain ation	Pote Impac	tion in ential et Area or No)
Building and Utilities:											
Roads and Railroads:											
Bridges:								· · · · · · · · · · · · · · · · · · ·			
	·										
Describe Potential Downs	Describe Potential Downstream Development:										
Potential impact area due to sudden failure of dam: Determined by breach routing. (See attached maps and/or other descriptions)											
Taken from Tech. Note 9: H _{BR} = Auxiliary Spillway Elevation Floodplain elevation											
= = ft.											
	A = Area of dam above floodplain elevation = sq. ft.										
V _S = F =	ac. 1	ft.									
$BR = \frac{V_S H_{BR}}{A} = \frac{x}{ac}$											
$Q_{\text{max}} = 1100 \text{ BR}^{1.35} = \underline{\hspace{1cm}} \text{cfs.}$ Use $\underline{\hspace{1cm}} \text{cfs}$											
Distance Downstream (ft)	0	500	1,000	1,500	2,000	2,500	3,000	5,000	7,500	10,000	15,000
Water Depth (ft)	H _{BR}	<u> </u>	<u> </u>				ļ	<u> </u>			
Q (cfs)	Qmax		<u> </u>]	<u> </u>	<u> </u>	L	<u> </u>		L	

The hazard classification and design should be re-evaluated if there is development or changes in the impact area or upstream watershed.

NOTE:

Inventory dams are described in NATIONAL INVENTORY AND MONITORING MANUAL, Part 505, MO505.05 and NATIONAL ENGINEERING MANUAL 520.21(f).

(All class b and c dams.

All class a dams with 6 feet overall height and storage of 50 or more acre-feet.

All class a dams with 25 feet overall height and storage of 15 or more acre-feet.)

²Definition of hazard classification in NATIONAL ENGINEERING MANUAL 520.21.

³/ See Rules and Regulations of the Missouri Dam and Reservoir Safety Council if overall dam height is greater than 35 feet.

⁴ See NATIONAL ENGINEERING MANUAL Supplement MO 520.23 and MO 520.28.

⁵/ This form may also be used for non-inventory size dams.

MO-ENG-C46

File

	1001. 4-77
Code:	Coop. Folder

Landowner:						Sheet 1 of 2
Address:					Field No.	
Designed by:		Date: _				
	СНЕСЬ	HAZARD CLASSII K FACTORS WHICH A		5 DAM		
E H	upplementary state r ittle or no potential bownstream valley is lazard classification	than 3000. ment limited to farm be oads. for future downstream as wide or wider than	development. at dam site.			
	_	DESIGN PROCE				
Emergency spills Emergency spills Emergency spills 2. For Drainage A Circle appropria Table A 10 Yr/24 Hr Rainfall Factor 5.0" 1.9 5.2" 2 5.4" 2.1 5.6" 2.4 5.8" 2.5	Table B RCN Factor 65 0.8 70 1 1.3 80 1.5 85 2	w depth + 1.0 ft. freeboar Table C	d = 2 ft. in spaces provide Storag Ratio 10 15	Factor 0.4 0.6 0.7 0.8	Table Aux. Spwy. Flow Depth 0.5' 1.0' 1.2' 1.5'	Factor 1.3 0.44 0.33 0.22
Storage Ratio:	Pool Area	= ()			
Auxiliary = Spillway Bottom Width =	Drainage Area T	= Roundaria Roun	Table C Factor Factor	Table D Factor		
Auxiliary = Spillway Depth	+ 1.0 Flow Depth (From Table E)	Ft. Freeboard =	·			

This design procedure is limited to Class A hazard ponds with drainage area 20 acres or less, effective height 20 feet or less, total height less than 35 feet, no pipe spillway, "Fair" or "Good" auxiliary spillway condition, and 1 to 10% auxiliary spillway exit slope. Trickle tubes may be used. Use Form MO-ENG-40 or Pond Program for larger ponds and structures.

MO-ENG-C46 Rev. 4-99
File Code: Coop. Folder
Sheet 2 of 2

LAYOUT

Landow	Landowner							
Surveye		T	P	Date				
Station	B.S.	H.I.	F.S. or grade rod	Top of Dam Elev.	Settled fill ht	Settlement	Slope stakes and remarks	
	 	<u> </u>						
		<u> </u>						
		<u> </u>				ļ <u>.</u>		
						<u> </u>		
					1			
						-		
]							
					<u> </u>			
					I			
Dam:	Elev. S	ettled Fil	ll:	TW:	ft.	Side slopes: U	JS: DS:	
	Auxilia	ry Spiliv	vay: Crest Elev		Width		π.	
		_ % allo	wed for settlement		Staked for	r (settled)	(unsettled) fill height	
1								
Sec	c							
'] •	Г R							
ŀ	<i>r</i>							
				1				

SUBPART C - DAMS

MO520.25(b)(2)(iii)

\$MO520.25 Clearing Reservoirs

- (b)(2)(iii) Inflow channels shall not be cleared upstream beyond the point where the contour representing the crest of the lowest ungated principal spillway inlet remains within the channel banks.
- (iv) For land treatment structures (grade stabilization), RC&D-CAT structures, and small floodwater structures (less than 3,000 height x storage) the minimum area to be cleared shall be as stated in 520.25(b)(2)(ii). The 400 feet shown in 520.25(b)(2)(ii) shall be from principal spillway inlet.

SUBPART C – DAMS

MO520.28(b)(3)

MO520.28 Potential impact area—class (a) dams of inventory size and all class (b) dams.

(b) Requirements.

- (3) Use Form MO-ENG-C82 to document the impact area and a letter similar to Exhibit in MO520.28 to inform the landowner. Other forms or maps are acceptable if they show the same information.
 - (4) Use breach routing procedures for all class (b) dams.
 - (5) The following procedures will be used in class (a) inventory size dams.
- (i) The person who approves the design drawings will determine that the proper method was used to define the impact area. Breach routing or a conservative approximation may be used.
- (ii) A conservative approximation normally used would be the area defined using data from the charts in Appendix B of Missouri Engineering Technical Note 9 for those sites meeting the applicable conditions.
 - (6) Advise owners that the hazard classification and design should be reevaluated if there is development or changes in the impact area.

PART 520 – SOIL AND WATER RESOURCES DEVELOPMENT

\$MO520.28(c)(3) MO520.28(c)(3)

(c) <u>Distribution.</u>

- (3) The description and/or maps of the potential impact area shall be submitted to the landowner or sponsor. It is the responsibility of the landowner or sponsor to transmit the description of potential impact area to:
 - (i) All landowners involved.
 - (ii) The local Soil and Water Conservation District.
 - (iii) The Missouri Dam and Reservoir Safety Program if the overall height is 35 feet or greater.
 - (iv) Any local government agency having zoning authority on the potential impact area.
- (4) If requested by the owner or sponsor, or if the owner or sponsor fails to act, NRCS shall distribute this information. The responsibility for distributing this information is delegated to the district conservationist by the state conservationist.

SAMPLE LETTER TO INFORM LANDOWNERS

MO 520.28

<Name of Office>
<Address of NRCS office>
<City, State Zip of NRCS office>
<NRCS Office phone number>

<date></date>
<name> <address> <city>, <state> <zip code=""></zip></state></city></address></name>
<salutation>:</salutation>
The Natural Resources Conservation Service (NRCS) has designed a dam on your property. The location, size, and other significant features regarding the dam are shown on the attached form.
The form shows information used to evaluate the area that would be flooded or impacted should there be a sudden failure of the dam. The hazard class and design were based on this information. The hazard classification and design should be re-evaluated if changes are made in the impact area downstream from the dam or in the watershed upstream of the dam.
Dam failures are rare and most failures are not of the sudden, catastrophic type. The NRCS believes your dam will serve you for many years. However, this information on the potential hazard in case of sudden failure is being furnished so everyone affected by the construction of this dam can be properly informed.
A copy of this letter and form are being sent to your local Soil and Water Conservation District and any local government agency having zoning authority on the potential impact area for their information. If the dam is 35 feet or greater in overall height, the Missouri Dam and Reservoir Safety Program will be sent a copy for their information.
Please contact me if you have questions or desire further information.
Sincerely,
<nrcs employee="" name=""></nrcs>

Atta	chments: Form MO-ENG-C82, MO-ENG-C46 or MO-ENG-46
Cc:	Soil and Water Conservation District
	Local agency having zoning authority on potential impact area
	Missouri Dam and Reservoir Safety Program (Only if dam is 35 feet or greater in height.

District Conservationist